

The background of the advertisement is a dark, metallic surface with a grid of stainless steel pipes. A large, glowing globe is centered in the middle of the page, showing the continents of North and South America. The lighting creates a sense of depth and texture on the pipes and the globe.

Indel
INOXIDABLES

CALIDAD
MUNDIAL
DE ORIGEN

Estados Unidos de América • Canadá • México • Guatemala • Colombia • Venezuela • Ecuador • Brasil • Chile



CALIDAD
MUNDIAL
DE ORIGEN

Indel
INOXIDABLES

Inoxidables de Laredo, INDEL, es la marca de tubería y conexiones de acero inoxidable de mayor calidad y presencia mundial. Su línea de productos abarca las conexiones roscadas y tubería con y sin costura, ideales para la conducción de fluidos de alta corrosión así como espacios que requieren una alta higiene.

Las conexiones INDEL se encuentran disponibles en tipo 304L y 316L y la tubería en cédulas 10S, 40S, 80S, 304L y 316L, con y sin costura.

Gracias a la alta exigencia y cuidado en su fabricación, INDEL es Calidad mundial de origen.



CODO 90°



CODO 45°



TAPÓN CACHUCHA



TAPÓN MACHO



TEE



TUERCA UNIÓN



MEDIO COPLE



REDUCCIÓN BUSHING



REDUCCIÓN CAMPANA



COPLÉ

Estándares y Especificaciones:

- Material: Acero Inoxidable tipo 304 y tipo 316
- Fundación de acuerdo a ASTM A351
- Roscas: NPT de acuerdo a ASME B1.20 1
- Medidas en conexiones 1/4 a 4"
- Fabricado Bajo Estándares ISO 9001:2000



**TUBERÍA
DE ACERO
INOXIDABLE
304L y 316L**
 con y sin costura

Diámetro Nominal		ASME B36.19M-2004 ESPEORES DE PARED (solo para tubería de acero inoxidable)				
DN*	DN**	D.E.	CED5S	CED10S	CED40S	CED80S
1/8	6	10.29	-	1.24	1.73	2.41
1/4	8	13.72	-	1.65	2.24	3.02
3/8	10	17.15	-	1.65	2.31	3.20
1/2	15	21.34	1.65	2.11	2.77	3.73
3/4	20	26.67	1.65	2.11	2.87	3.91
1	25	33.40	1.65	2.77	3.38	4.55
1 1/4	32	42.16	1.65	2.77	3.56	4.85
1 1/2	40	48.26	1.65	2.77	3.68	5.08
2	50	60.33	1.65	2.77	3.91	5.54
2 1/2	65	73.03	2.11	3.05	5.16	7.01
3	80	88.90	2.11	3.05	5.49	7.62
3 1/2	90	101.60	2.11	3.05	5.74	8.08
4	100	114.30	2.11	3.05	6.02	8.56
5	125	141.30	2.77	3.40	6.55	9.53
6	150	168.28	2.77	3.40	7.11	10.97
8	200	219.08	2.77	3.76	8.18	12.70
10	250	273.05	3.40	4.19	9.27	12.70
12	300	323.85	3.96	4.57	9.53	12.70
14	350	355.60	3.96	4.78	9.53	12.70
16	400	406.40	4.19	4.78	9.53	12.70
18	450	457.20	4.19	4.78	9.53	12.70
20	500	508.00	4.76	5.54	9.53	12.70
22	550	558.80	4.78	5.54	-	-
24	600	609.60	5.54	6.35	9.53	12.70
26	650	660.40	-	-	-	-
28	700	711.20	-	-	-	-
30	750	762.00	6.35	7.92	-	-
32	800	812.80	-	-	-	-
34	850	863.60	-	-	-	-
36	900	914.40	-	-	-	-
38	950	965.20	-	-	-	-
40	1000	1016	-	-	-	-
42	1050	1066.8	-	-	-	-
44	1100	1117.6	-	-	-	-

DN* Medidas en pulgadas.
DN** Medidas en milímetros.

The logo for Indel INOXIDABLES is centered on a white circular background. The word "Indel" is written in a black, elegant cursive script, with a small red dot above the letter 'i'. Below "Indel", the word "INOXIDABLES" is written in a clean, black, uppercase sans-serif font.

Indel
INOXIDABLES